

SNMP WiseWay 3.2 external card

TYPE: External SNMP adapter

MODEL: WiseWay 3.2 external



COMPATIBILITY

- UPS COVER MY30K, MZ

SPECIFICATION

Model	WiseWay 3.2 external
Type	External SNMP adapter
RAM	1 GB
Flash memory	4 GB
Ports	RJ45 – LAN, auto-sense 10/100 Mbps, DB9: RS232, RJ45: RS485, RJ45: RS232/RS485
Supported languages	Polish, English, Simplified Chinese, Traditional Chinese, Spanish, Korean, Russian
Power	9-15V, 1A
Working environment	Temperature: 5°C - 50°C, Humidity: 5% - 95% (no condensation)
Storage temperature	-25°C - 70°C
MIB	RFC1628, Wiseway3.0
Size(lxWxG)	85x77x30mm
Protocols	TCP/IP, IP4, IP6, SNMPv1,2,3, NTP, HTTP, HTTPS, SMTP, DHCP, ModbusTCP, BACnet, SSL, STARTTLS, TLS, Wake-on-LAN, RADIUS
Optional equipment	
Environmental conditions sensor (temperature/humidity)	
Software	
WiseClose - shuts down computers/server in case of power failure (Windows platform)	
WiseFind - software to detect a card on the LAN and perform initial configuration	
WiseInsight - software to monitor UPS operation (more devices can be monitored)	

Due to the continuous improvement of the product, we reserve the right to change parameters without prior notice.